



Model CNY220PT

'C' Series Powered by Cummins Engine



Rating:	220 kW Standby at 60 Hz
Make:	Cummins
Type:	4 Cycle.
Engine Model:	QSL9G2
Gross Engine Power Output:	364 BHP at 1800 rpm.
Cylinder:	6 in Line
Bore X Stroke:	114 x 145 mm.
Displacement:	
Piston Speed:	8.7 m / Sec.
Compression Ration:	16.8 : 1
Fuel Consumption:	71 Lts./Hrs.
Aspiration:	Turbocharged And Air cooled
Electrical System:	24 volts.
Oil Total System Capacity:	
Electric Governor:	Electronic



PTOM220C



Weight (kgs) : 1778 kgs
Dimensions (cm) : L 290 x W 124 x H 173 cm

Control System: Set Mounted Dale 3100 Autostart Control Panel.

Engine: All heavy Duty, water cooled Diesel Engine, include starter and battery charging alternator; high ambient set mounted radiator cooling system.

Alternator: Brushless design, screen protected, fan ventilated, drip proof in accordance with IP 21. Insulation class H, radio interference suppression, voltage regulation is maintained within +/- 1% from no load to full load at any power factor between 0.8 lagging and unity, inclusive of a speed variation of upto 4%.

Electrical System: 24 Volt system with battery charging alternator.

Documentation: A full set of operation and maintenance manuals.

Factory Test: The generator set is load tested before dispatch.

Authorized Distributor:

Partech Industries, Inc.

5773 NW 151 Street
 Miami Lakes, Fl 33014 USA

Tel 305-751-0160
 Fax 305-757-9809
 E-MAIL: sales@partech.us

www.partech.us

